FRITZ

FCP-400

Floor Finish Stripper

DESCRIPTION: FCP-400 Floor Finish Stripper is a powerful stripper that is strong enough to remove hardened floor waxes and built-up layers of water-resistant floor finishes.

LIMITATIONS: Never flood a Fritztile floor during stripping. Do not pour FCP-400 Floor Finish Stripper directly onto the tile surface. Do not use FCP-400 as a general purpose floor cleaner.

SURFACE PREPARATION: Move furniture/ equipment as necessary. Sweep the floor with a broom or dust mop.

MIXING & APPLICATION: Use 1 part FCP-400 stripper to 20 parts clean water (6 oz. stripper per gallon of water). Apply with a mop or floor machine. For the fastest removal of wax or finish, use a floor machine and an abrasive pad. If areas under desks and along walls, or where heavy traffic is common have multiple coats of finish, use a solution of 1 part stripper to 3 parts water. Avoid splashing solution on painted base boards or walls. If this happens spotting may occur. Pick up soiled scrubbing solution with a mop or wet pick-up vacuum. Rinse the floor thoroughly before applying floor finish.

NOTE: Strong concentrations on unwaxed floors may cause discoloration.

COLOR: Dark green.

SHELF LIFE: One year.

CAUTION: Harmful if swallowed. This solution contains sodium silicates. May cause skin and eye irritation. Avoid skin contact, eye contact or contact with mucus membranes. Always use adequate ventilation when working with FCP-400. Keep this container capped when it is not in use. Keep out of reach of children. If skin or eye contact occurs, flush thoroughly with water. If irritation persists, see a physician immediately. If swallowed, DO NOT INDUCE VOMITING. Drink large amounts of water or milk. Call a physician immediately.

NOTES:

1 U.S. GALLON / 3.8 LITERS

For further information, please contact: Fritz Industries, Inc. • 500 Sam Houston Rd. • Mesquite, TX 75149
Toll Free: 1-800-955-1323 • Office: (972) 285-5471 • Fax (972) 270-0179
email: tilesales@fritzind.com • www.fritztile.com

EU050803