

FRITZ

P



Acrylic Primer and Admixture

Fritz P-100 Primer is a high-strength acrylic polymer specifically designed to be used as a primer for Fritz F-10 Self-Leveling Underlayment, Poz Patch I and Poz Patch II. It can also be used as an admixture to increase the flexural strength of F-10 over wood and steel decks. Extremely durable, P-100 exhibits excellent adhesion to a variety of porous & non-porous surfaces and can also be used on substrates such as masonry, brick, ceramic tile and quarry tile.

Surface Preparation: The substrate surface must be sound, thoroughly clean and free of wax, dust, dirt, oil and grease. Note that bond strength will be only as strong as the adhesion of the sealer, adhesive or residue to the substrate. This means that P-100 will bond with agents present on top of the substrate surface instead of with the actual substrate if the surface is not properly cleaned before application. P-100 can not repair unfit substrates.

Surface Types & Limitations:

Steel Surfaces and Special Surfaces: Slick surfaces such as ceramic tile, terrazzo and steel should be primed with Fritz P-100 Primer diluted at a ratio of 1 gallon of primer to 1/2 gallon of clean water. Extremely porous substrates may need to be primed twice.

Mixing and Application:

Shake well. Dilute P-100 with an equal part of clean water in a separate bucket or container. Using a broom or hand brush, apply P-100 to a properly prepared substrate. Allow to dry 1 hour, but no longer than 12 hours. Do not allow pooling or puddling.

P-100 as an Admixture: To use P-100 as an admixture for F-10 Self-Leveling Underlayment, add 1/2 gallon P-100 concentrate to 1 gallon of plain water and mix thoroughly. Under agitation, add 1 bag of F-10. Mix well for 2-3 minutes.

Coverage: 250 square feet per diluted gallon.

Packaging: 1 gal, 5 gal concentrate.

Note: Fritz P-100 Acrylic Primer is sediment-free and stable to a minimum of five cycles of freezing at 5°F to 78°F. After prolonged storage, especially in cold weather, the emulsion should be stirred.

Shelf Life & Warranty: Fritz P-100 Acrylic Primer has a shelf life of one year in an unopened container. Avoid freezing conditions and excessive heat. Manufacturer's warranty is limited to replacement of defective material.

Safety Precautions: This product contains ingredients that can irritate skin, eyes and lungs. Use reasonable care and cleanliness when handling P-100 to avoid contact with these bodily areas. Make sure work areas are always well ventilated. Provide forced ventilation if necessary. Use rubber gloves or other protective clothing. In case of skin contact, wash with soap and water. In case of eye contact, thoroughly flush eyes with water for 15 minutes. If skin rash occurs, or if eye irritation persists, consult a physician as soon as possible.

KEEP OUT OF REACH OF CHILDREN.

Fritz Industries Inc.

Manufactured at: 500 Sam Houston Road, Mesquite, TX 75149
Phone:(972)285-5471 Toll Free:1-800-955-1323 Fax 1-972-270-0179

e-mail us at: tilesales@fritzind.com

Visit our website: www.fritztile.com

EU060603