



ADHESIVE AND TROWEL REQUIRMENTS

TECHNICAL SUPPORT 800.345.6202

General Requirements	FA-88	FA-1100
Max Moisture Levels	10 lbs. / 90% RH	7 lbs. / 87% RH
Indoor Installations	Yes	Yes
Wet Setting Required	Yes	Yes
Usage over Existing	No	No
Old Adhesive	No	No
Radiant Heat	Yes	Yes

Coarse Concrete	FA-88	FA-1100
Adhesive Recommendations	Yes	N/A
Trowel	1/8 x 1/8 x 1/8 U	N/A
Gallon Coverage (sq ft / gallon)	80-90	N/A

Smooth Concrete	FA-88	FA-1100
Adhesive Recommendations	Yes	Yes
Trowel	1/8 x 1/8 x 1/8 U	1/16 x 1/16 x 1/16 sq
Gallon Coverage (sq ft / gallon)	100-110	110-140

Underlayment	FA-88	FA-1100
Adhesive Recommendations	Yes	Yes
Trowel	1/8 x 1/8 x 1/8 U	1/16 x 1/16 x 1/16 sq
Gallon Coverage (sq ft / gallon)	100-110	110-140

Wood	FA-88	FA-1100
Adhesive Recommendations	N/A	Yes
Trowel	N/A	1/16 x 1/16 x 1/16 sq
Gallon Coverage (sq ft / gallon)	N/A	110-140

Steel	FA-88	FA-1100
Adhesive Recommendations	N/A	Yes
Trowel	N/A	1/16 x 1/16 x 1/16
Gallon Coverage (sq ft / gallon)	N/A	110-140

For more information visit www.fritztile.com or call 800-345-6202.